

Arbo Polymer Putty

Arbo Polymer Putty is a one part Water Based Acrylic Putty designed to combine the benefits of modern polymer technology with the ease of cartridge application for use in many traditional glazing applications.

MAIN APPLICATIONS

Recommended for the face glazing of wooden windows and traditionally painted steel windows. Recommended for patch repairs to putty facings on wood and steel windows. **NB**: Not recommended for use with double glazed units or laminated glass.

APPLICATION

Glazing should be carried out in accordance with BS8000 Part 7:1990 and the relevant clauses of BS6262. Arbo Polymer Putty is supplied in polyethylene 310ml cartridges and can be applied using an Arbo Caulking Gun.

Extrude the Polymer Putty firmly against substrates to ensure full contact. Strike off using a wetted glazing knife to achieve a smooth finish.

NB: Only for use in dry weather – do not apply when rain is imminent

APPLICATION INSTRUCTIONS

Joint preparation

All glazing surfaces must be clean, dry and free from all contamination.





TECHNICAL DATA	
Skin Time at 20º C/65 % RH:	30 minutes
Application Temperature::	+ 5º C to + 40º C
Service Temperature:	- 20º C to + 70ºC
Cure Rate at 20º C/65 % RH:	Dependent upon sealant depth, ambient temperature and humidity
Chemical Resistance:	Fair resistance to most dilute acids and alkalis. Poor resistance to organic solvents
Service Life:	15 years+
UV Resistance:	Good
Paintability:	Painting will extend the life of the product. Paintable with most common paint finishes once product has skinned and firmed. A trial area

PACKAGING

25 x 310ml Polyethylene Cartridges per box. Polyethylene Nozzles are included in each box.

COLOURS

Natural

STORAGE LIFE

12 months in original unopened packaging stored in a cool, dry place out of direct sunlight.

HEALTH AND SAFETY.

No particular hazards with this product but please consult Material Safety Data Sheet for full information

ACCESSORIES

Cleaners

is recommended for compatibility and appearance

Arbo Cleaner No.17- 1 Litre Tin (Xylene based - not suitable for usewith plastics or delicate finishes) Arbo Cleaner No. 16 - 1 Litre Tin (Alcohol Based)

Ancillary Equipment

Polyethylene Nozzles Arbo Caulking Guns Arbo Putty Knife

IMPORTANT: The information in this leaflet is given in good faith and based on results gained from experience and tests. However, all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Goods are supplied subject to the Company's terms and conditions of sales, a copy

www.arbo.co.uk

CARLISLE® Adshead Ratcliffe & Co Ltd. United Kingdom

of which is available on request.

Derby Road | Belper Derbyshire

DE56 1WJ United Kingdom T +44 (0)1773 826661 E arbo@arbo.co.uk F +44 (0)1773 821215