

## for fast, precise positioning and fixing



The Nico 3D Adjustable Door Hinge is part of the Nico range of heavy duty, maintenance-free door hinges developed for long-life performance under the most arduous conditions.

The 3D Adjustable Door Hinge is the ideal solution for high performance applications. Featuring low-friction bearings for smooth door opening, it offers guaranteed reliable, maintenancefree operation.

The 3D Hinge is available in a selection of corrosion resistant finishes including polished chrome, brass and Supercoat 500 - achieving Grade 5 (exceptionally high resistance to corrosion) to BS1670:2007. It can also be powder coated to any RAL colour on request.

The 3D Hinge is fully adjustable in three directions for precise positioning and fixing. For ease and speed of installation, the patented design allows the hinge to remain fixed to the door during the adjustment process.

The 3D Hinge is also available in an 'Open Out' version for enhanced security.



**SBD Member Company UK** manufacture

**Patented innovative** design


Low friction bearings

Easy 3D adjustment

**Standard and Open Out Options** 

Choice of finishes. including polished chrome and brass

**Complies with BS** EN1935:2002




TOP: 4915 3D Adjustable Door Hinges in (left to right) white powder coating, Supercoat 500 and yellow zinc.

ABOVE: Polished brass and polished chrome.

For sales, call 01255 422333 or email sales@nico.co.uk



#### Hinge Adjustment Sequence



#### **Vertical Adjustment**

Slacken 'A' screws on hinges. Adjust door to correct height and retighten screws.

#### **Horizontal Adjustment**

Partially slacken 'B' screws on hinge. Turn 'C' screw anticlockwise to move leaves apart and clockwise to bring them together. Retighten 'B' screws after adjustment. NOTE. Hinges supplied set with 2mm hinge gap.

#### **Seal Compression Adjustment**

Slacken 'B' screws. Adjust door to correct compression on seal and retighten screws.

#### Available to order

Products indicated with the Telephone Symbol are available to order only. Please ring for details and lead times.





ISO 9001 Cert No: Q 0935

#### Nico Manufacturing Ltd

Oxford Road, Clacton-on-Sea Essex CO15 3TJ, England.

Tel: 01255 422333 Fax: 01255 432909 E-mail: sales@nico.co.uk Web: www.nico.co.uk

# 3d adjustable door hinge


## **Technical Data**

The Nico 3D Adjustable Door Hinge features an innovative, patented design that allows independent adjustment in all three axes by 4mm key.

- +/- 2.5mm Height
- +/- 2mm Side
- +/- 2mm Depth (compression)

There are no shims and all adjustments can be carried out in situ.

The Open Out 3D Hinge version is made to order and has a special security feature. This makes it the ideal option for use when the hinge roll is outside the door. Contact the Nico Sales Team for details.



### **3D Adjustable Hinge**

Finish	Size	Product Code	Max. Adjusted Door Weight	Box Quantity
Supercoat 500	92 x 92 x 14mm/2.7mm	4915S5	80kg	10
White	92 x 92 x 14mm/2.7mm	4915WH	80kg	10
Black	92 x 92 x 14mm/2.7mm	4915BL	80kg	10
Chrome	92 x 92 x 14mm/2.7mm	4915CH	80kg	10
Polished Brass	92 x 92 x 14mm/2.7mm	4915PB	80kg	10
	able Hinge: Open Out Door			
4915 3D Adjust	able Hinge: Open Out Door	Product Code	Max. Adjusted	Box Quantity
Finish	Size		Door Weight	· ·
Finish		Product Code 34915SECS5	•	Box Quantity
Finish	Size		Door Weight	· ·
Finish Supercoat 500	Size 92 x 92 x 14mm/2.7mm	34915SECS5	Door Weight 80kg	10
Finish Supercoat 500 White	Size  92 x 92 x 14mm/2.7mm  92 x 92 x 14mm/2.7mm	<b>3</b> 4915SECS5 <b>3</b> 4915SECWH	Door Weight 80kg 80kg	10

For sales, call 01255 422333 or email sales@nico.co.uk